

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2021

Version-No. 2 (replaces version 1)

Revision: 15.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1. Product identifier**
- Trade name / Article-No: ***Dockskin 200***
- Article number: 5820-1000
- **1.2. Relevant identified uses of the substance / mixture or uses advised against**
Restricted to professional users.
- **Application of the substance / the mixture** Primer
- **1.3. Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SIGA Cover AG
Rüt mattstr. 7
CH-6017 Ruswil
Tel. + 41 (0) 41 499 69 69
www.siga.swiss
- **Further information obtainable from:** technik@siga.swiss
- **1.4. Emergency telephone number:** + 41 (0) 41 499 69 69 during office hours from 8:00 am - 5 pm

SECTION 2: Hazards identification

- **2.1. Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008 - GHS/CLP**
Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 2 H351 Suspected of causing cancer.
STOT SE 3 H335 May cause respiratory irritation.
STOT RE 2 H373 May cause damage to the respiratory system through prolonged or repeated exposure.
Route of exposure: Inhalation.

- **2.2. Label elements**

- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labelling:**

Diphenylmethane diisocyanate (isomer mixture)

- **Hazard statements**

H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2021

Version-No. 2 (replaces version 1)

Revision: 15.12.2021

Trade name / Article-No: **Dockskin 200**

(Contd. of page 1)

H335 May cause respiratory irritation.

H373 May cause damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

- **Precautionary statements**

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

- **Additional information:**

Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

- **2.3. Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

Registry-No's	Identification / Classification GHS-CLP	%
CAS: 101-68-8 EINECS: 202-966-0 Reg.nr.: 01-2119457014-47-XXXX	diphenylmethane-4,4'-diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; C ≥ 5 %	30-40%
CAS: 9048-57-1 NLP: 500-028-8	4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with α-hydro-ω-hydroxypoly(oxy-1,2-ethanediyl) Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317; STOT SE 3, H335	20-30%
CAS: 5873-54-1 EINECS: 227-534-9 Reg.nr.: 01-2119480143-45-XXXX	diphenylmethane-2,4'-diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; C ≥ 5 %	10-20%
CAS: 9016-87-9	diphenylmethane-diisocyanate, isomers and homologous Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; C ≥ 5 %	10-20%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2021

Version-No. 2 (replaces version 1)

Revision: 15.12.2021

Trade name / Article-No: **Dockskin 200**

(Contd. of page 2)

CAS: 25686-28-6 NLP: 500-040-3 Reg.nr.: 01-2119457013-49-XXXX	methylenediphenyl diisocyanate, modified Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; C ≥ 5 %	10-20%
CAS: 2536-05-2 EINECS: 219-799-4	2,2'-methylenediphenyl diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; C ≥ 5 %	≥0.1-<1%
CAS: 4083-64-1 EINECS: 223-810-8	tosyl isocyanate Resp. Sens. 1, H334; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335, EUH014, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % STOT SE 3; H335: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	≥0.1-<0.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1. Description of first aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

· **After skin contact:**

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning agent.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Call for a doctor immediately.

· 4.2. Most important symptoms and effects, both acute and delayed

Asthma attacks

Allergic reactions

· 4.3. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1. Extinguishing media

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2. Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Isocyanates

Nitrogen oxides (NO_x)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2021

Version-No. 2 (replaces version 1)

Revision: 15.12.2021

Trade name / Article-No: **Dockskin 200**

(Contd. of page 3)

Traces: Hydrogen cyanide (HCN)

· **5.3. Advice for firefighters**· **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· **6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Particular danger of slipping on leaked/spilled product.

Use respiratory protective device against the effects of fumes/dust/aerosol.

· **6.2. Environmental precautions:** No special measures required.· **6.3. Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4. Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1. Precautions for safe handling**

Appropriate regular employee training.

Handle the substance preferably in closed system

Enclosure or extractor facilities are required.

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Not less than 3-5 air exchanges per hour

Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.

Spraying: in vented cabin with laminar air flow

Wear protective gloves/protective clothing/eye protection/face protection.

Use only in well ventilated areas.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

regular check up, maintenance and cleaning of equipment and machines

Avoid contact with skin and eyes.

It is advised against using the product if there is a sensitivity of the airways or skin (asthma, chronic bronchitis, chronic skin disease)

Handling procedures must be well documented.

additional to professional application with multiple and/or significant contact

limit the exposure to 4 hours

· **General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing

Avoid contact with the skin.

· **7.2. Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:** Keep container tightly closed.· **Information about storage in one common storage facility:** Observe the national regulations.· **Further information about storage conditions:** Protect from humidity and water.· **7.3. Specific end use(s)** No further relevant information available.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2021

Version-No. 2 (replaces version 1)

Revision: 15.12.2021

Trade name / Article-No: **Dockskin 200**

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1. Control parameters

· Ingredients with limit values that require monitoring at the workplace:

· DNELs

101-68-8 diphenylmethane-4,4'-diisocyanate

Dermal DNEL short term 50 mg/kg (human being)

Inhalative DNEL short term 0.1 mg/m³ (human being)DNEL long term 0.05 mg/m³ (human being)

5873-54-1 diphenylmethane-2,4'-diisocyanate

Dermal DNEL short term 50 mg/kg (human being)

Inhalative DNEL short term 0.1 mg/m³ (human being)DNEL long term 0.05 mg/m³ (human being)

9016-87-9 diphenylmethane-diisocyanate, isomers and homologous

Dermal DNEL short term 50 mg/kg (human being)

DNEL long term 0.05 mg/kg (human being)

Inhalative DNEL short term 0.1 mg/m³ (human being)

25686-28-6 methylenediphenyl diisocyanate, modified

Dermal DNEL short term 28.7 mg/kg (human being)

Inhalative DNEL short term 0.1 mg/m³ (human being)DNEL long term 0.05 mg/m³ (human being)

2536-05-2 2,2'-methylenediphenyl diisocyanate

Dermal DNEL short term 50 mg/kg (human being)

Inhalative DNEL short term 0.1 mg/m³ (human being)DNEL long term 0.05 mg/m³ (human being)

· PNECs

101-68-8 diphenylmethane-4,4'-diisocyanate

PNEC- Freshwater 1 mg/l (not specified)

PNEC-seawater 0.1 mg/l (not specified)

PNEC-periodic release 10 mg/l (not specified)

PNEC-Freshwater sediment 1 mg/kg (not specified)

PNEC-soil 1 mg/kg (not specified)

PNEC-wastewater treatment plant 1 mg/l (not specified)

5873-54-1 diphenylmethane-2,4'-diisocyanate

PNEC- Freshwater 1 mg/l (not specified)

PNEC-seawater 0.1 mg/l (not specified)

PNEC-soil 1 mg/kg (not specified)

PNEC-wastewater treatment plant 1 mg/l (not specified)

9016-87-9 diphenylmethane-diisocyanate, isomers and homologous

PNEC- Freshwater >1 mg/l (not specified)

PNEC-seawater >0.1 mg/l (not specified)

PNEC-soil >1 mg/kg (not specified)

PNEC-wastewater treatment plant >1 mg/l (not specified)

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2021

Version-No. 2 (replaces version 1)

Revision: 15.12.2021

Trade name / Article-No: **Dockskin 200**

(Contd. of page 5)

25686-28-6 methylenediphenyl diisocyanate, modified

PNEC- Freshwater 1 mg/l (not specified)
 PNEC-seawater 0.1 mg/l (not specified)
 PNEC-soil 1 mg/kg (not specified)
 PNEC-wastewater treatment plant 1 mg/l (not specified)

2536-05-2 2,2'-methylenediphenyl diisocyanate

PNEC- Freshwater >1 mg/l (not specified)
 PNEC-seawater >0.1 mg/l (not specified)
 PNEC-soil >1 mg/kg (not specified)
 PNEC-wastewater treatment plant >1 mg/l (not specified)

Ingredients with biological limit values:**101-68-8 diphenylmethane-4,4'-diisocyanate**

BMGV (Great Britain) 1 µmol creatinine/mol
 Medium: urine
 Sampling time: At the end of the period od exposure
 Parameter: isocyanate-derived diamine

5873-54-1 diphenylmethane-2,4'-diisocyanate

BMGV (Great Britain) 1 µmol creatinine/mol
 Medium: urine
 Sampling time: At the end of the period od exposure
 Parameter: isocyanate-derived diamine

2536-05-2 2,2'-methylenediphenyl diisocyanate

BMGV (Great Britain) 1 µmol creatinine/mol
 Medium: urine
 Sampling time: At the end of the period od exposure
 Parameter: isocyanate-derived diamine

CAS No.	Designation of material	%	Type	Value	Unit
---------	-------------------------	---	------	-------	------

101-68-8 diphenylmethane-4,4'-diisocyanate

WEL (Great Britain) Short-term value: 0.07 mg/m³
 Long-term value: 0.02 mg/m³
 Sen; as -NCO

5873-54-1 diphenylmethane-2,4'-diisocyanate

WEL (Great Britain) Short-term value: 0.07 mg/m³
 Long-term value: 0.02 mg/m³
 Sen; as -NCO

9016-87-9 diphenylmethane-diisocyanate, isomers and homologous

WEL (Great Britain) Short-term value: 0.07 mg/m³
 Long-term value: 0.02 mg/m³
 Sen; as -NCO

2536-05-2 2,2'-methylenediphenyl diisocyanate

WEL (Great Britain) Short-term value: 0.07 mg/m³
 Long-term value: 0.02 mg/m³
 Sen; as -NCO

4083-64-1 tosyl isocyanate

WEL (Great Britain) Short-term value: 0.07 mg/m³
 Long-term value: 0.02 mg/m³
 Sen; as -NCO

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2021

Version-No. 2 (replaces version 1)

Revision: 15.12.2021

Trade name / Article-No: **Dockskin 200**

(Contd. of page 6)

- **8.2. Exposure controls**
limit the exposure to:
8 hours
additional to professional application with multiple and/or significant contact
limit the exposure to 4 hours
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:** Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**
Use suitable respiratory protective device in case of insufficient ventilation:
At spray application respiratory protection must be worn.
- **Hand protection** Protective gloves
- **Material of gloves** A Nitrile rubber - NBR: AlphaTec® (> 0,4 mm)
- **Eye/face protection** Safety glasses
- **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1. Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Fluid
- **Colour:** Whitish
- **Odour:** Weak, characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** 208 °C
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** Not determined.
- **Upper:** Not determined.
- **Flash point:** 212 °C
- **Auto-ignition temperature:** Product is not selfigniting.
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity** Not determined.
- **Dynamic at 20 °C:** ca. 420 mPas
- **Solubility**
- **water:** Not miscible or difficult to mix.
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure:** Not determined.
- **Density and/or relative density**
- **Density at 20 °C:** ca. 1.17 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **9.2. Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Ignition temperature:** >400 °C
- **Explosive properties:** Product does not present an explosion hazard.
- **Change in condition**
- **Evaporation rate** Not determined.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2021

Version-No. 2 (replaces version 1)

Revision: 15.12.2021

Trade name / Article-No: **Dockskin 200**

(Contd. of page 7)

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1. Reactivity**
see item 10.3
No further relevant information available.
- **10.2. Chemical stability** Stable when stored and used properly.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3. Possibility of hazardous reactions** No dangerous reactions known.
- **10.4. Conditions to avoid** No further relevant information available.
- **10.5. Incompatible materials:** No further relevant information available.
- **10.6. Hazardous decomposition products:** Isocyanates

SECTION 11: Toxicological information

- **11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.
- **LD/LC₅₀ values relevant for classification:**

101-68-8 diphenylmethane-4,4'-diisocyanate

Oral	LD ₅₀	>2,000 mg/kg (rat) (84/449/EWG, B.1)
Dermal	LD ₅₀	>9,400 mg/kg (rabbit) (OECD 402)
Inhalative	LC ₅₀ /4 h	11 mg/l (x00) (Calculation (ATE))

9048-57-1 4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with α-hydro-ω-hydroxypoly(oxy-1,2-ethanediyl)

Inhalative LC₅₀/4h_(dust,mist) 0.49 mg/l (rat)

5873-54-1 diphenylmethane-2,4'-diisocyanate

Oral	LD ₅₀	>2,000 mg/kg (rat) (84/449/EWG, B.1)
Dermal	LD ₅₀	>9,400 mg/kg (rabbit) (OECD 402)
Inhalative	LC ₅₀ /4 h	11 mg/l (Ratte) (Calculation (ATE))

9016-87-9 diphenylmethane-diisocyanate, isomers and homologous

Oral	LD ₅₀	>10,000 mg/kg (rat)
Dermal	LD ₅₀	>9,400 mg/kg (rabbit)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2021

Version-No. 2 (replaces version 1)

Revision: 15.12.2021

Trade name / Article-No: **Dockskin 200**

(Contd. of page 8)

Inhalative LC₅₀ /4 h 11 mg/l (x00) (Calculation (ATE))**25686-28-6 methylenediphenyl diisocyanate, modified**Oral LD₅₀ 5,001 mg/kg (rat)Dermal LD₅₀ 9,401 mg/kg (rabbit)Inhalative LC₅₀/4h_(dust,mist) 0.49 mg/l (rat)**2536-05-2 2,2'-methylenediphenyl diisocyanate**Oral LD₅₀ >2,000 mg/kg (rat)Dermal LD₅₀ >9,400 mg/kg (rabbit)Inhalative LC₅₀ /4 h 11 mg/l (Ratte) (Calculation (ATE))**4083-64-1 tosyl isocyanate**Oral LD₅₀ 2,600 mg/kg (rat)**Note:**

diphenylmethane-diisocyanate:

The test atmosphere generated in the animal study is not representative of workplace environments, how the substance is placed on the market, and how it can reasonably be expected to be used. Therefore the test result cannot be directly applied for the purpose of assessing hazard. Based on expert judgment and the weight of the evidence, a modified classification for acute inhalation toxicity is justified.

- **Skin corrosion/irritation** Causes skin irritation.

- **Serious eye damage/irritation** Causes serious eye irritation.

- **Respiratory or skin sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- **Carcinogenicity** Suspected of causing cancer.

- **STOT-single exposure** May cause respiratory irritation.

- **STOT-repeated exposure**

May cause damage to the respiratory system through prolonged or repeated exposure. Route of exposure:
Inhalation.

- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1. Toxicity**

- **Aquatic toxicity:**

101-68-8 diphenylmethane-4,4'-diisocyanateLC₅₀ >1,000 mg / l / 96h (fish)EC₅₀ >1,000 mg / l / 24h (water flea - daphnia)IC₅₀ >1,640 mg / l / 72h (algae)**5873-54-1 diphenylmethane-2,4'-diisocyanate**LC₅₀ >1,000 mg / l / 96h (Zebrafish - Danio rerio)EC₅₀ >1,000 mg / l / 24h (water flea - daphnia)IC₅₀ >1,640 mg / l / 72h (Chlorophyceae - Scenedesmus subspicatus)**9016-87-9 diphenylmethane-diisocyanate, isomers and homologous**LC₅₀ >1,000 mg / l / 96h (fish)EC₅₀ >1,000 mg / l / 24h (water flea - daphnia)EC₅₀ >1,640 mg / l / 72h (algae)

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2021

Version-No. 2 (replaces version 1)

Revision: 15.12.2021

Trade name / Article-No: **Dockskin 200**

(Contd. of page 9)

25686-28-6 methylenediphenyl diisocyanate, modifiedLC₅₀ 1,001 mg / l / 96h (fish)EC₅₀ 1,001 mg / l / 24h (water flea - daphnia)EC₅₀ 1,641 mg / l / 72h (algae)**2536-05-2 2,2'-methylenediphenyl diisocyanate**LC₅₀ >1,000 mg / l / 96h (fish)EC₅₀ >1,000 mg / l / 24h (water flea - daphnia)EC₅₀ >1,640 mg / l / 72h (Chlorophyceae - Scenedesmus subspicatus)

- **12.2. Persistence and degradability** No further relevant information available.
- **12.3. Bioaccumulative potential** No further relevant information available.
- **12.4. Mobility in soil** No further relevant information available.
- **12.5. Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.6. Other adverse effects**
- **Behaviour in sewage processing plants:**
- **Remark:**
At correct sewage disposal in small quantities to biological sewage plants failures of the activated sludge are not expected.
- **Additional ecological information:**
- **General notes:** Not known to be hazardous to water.

SECTION 13: Disposal considerations

- **13.1. Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
Non contaminated packagings may be recycled.
Empty contaminated packagings thoroughly. Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1. UN number or ID number**
- **ADR, IMDG, IATA** Void
- **14.2. UN proper shipping name**
- **ADR, IMDG, IATA** Void
- **14.3. Transport hazard class(es)**
- **Class** Void
- **14.4. Packing group**
- **ADR, IMDG, IATA** Void
- **14.5. Environmental hazards:** Not applicable.
- **14.6. Special precautions for user** Not applicable.
- **14.7. Maritime transport in bulk according to IMO instruments** Not applicable.

SECTION 15: Regulatory information

- **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
See position no 2 - Hazards Identification

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2021

Version-No. 2 (replaces version 1)

Revision: 15.12.2021

Trade name / Article-No: **Dockskin 200**

(Contd. of page 10)

- **National regulations:**
- **Other regulations, limitations and prohibitive regulations:** Restricted to professional users.
- **15.2. Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH014 Reacts violently with water.
- EUH204 Contains isocyanates. May produce an allergic reaction.

- **Department issuing SDS:** Safety & Environment

- **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Resp. Sens. 1: Respiratory sensitisation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1B: Skin sensitisation – Category 1B
- Carc. 2: Carcinogenicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2