

Protecto ENERGY PLATE LINER®



The Only Self-Adhesive Air and Moisture Barrier Between the Floor Deck and Wall Plate

Protecto Energy Plate Liner[®] is designed specifically for conforming and sealing off the air gaps between the floor deck and the exterior wall plates. The unique peel and stick adhesive bottom of Protecto Energy Plate Liner allows for easy and precise placement. The 1/4" closed cell foam forms a gasket seal beneath the exterior wall plate virtually eliminating any air drafts resulting in a tremendous amount of heating and air conditioning energy savings.

Helps reduce energy costs by stopping air conditioning and heating loss between the wood floor and the wall plate

FEATURES & BENEFITS

- The only peel and stick 1/4" closed cell foam plate liner that totally stops air and moisture infiltration between the wood floor and wall plate
- Can be used in residential, commercial and multi-family construction
- Self-adhering for easy and precise placement
- Exceeds all local, state and national building codes
- Convenient $3^{1}/_{2}$ " and $5^{1}/_{2}$ " widths

- Conforms and seals off irregularities between substrates (i.e. warped wood to wood, metal frame to concrete, etc.)
- Stops dangerous carbon monoxide from entering the home from garage sill areas
- Extremely resilient, will not rot or deteriorate with age
- Adheres to wood, concrete, metal, block, vinyl and foam surfaces



Protecto ENERGY PLATE LINER®

APPLICATION:

Areas to be sealed must be clean and dry. Align Protecto Energy Plate Liner with the exterior perimeter of your floor deck. As you begin rolling out the Protecto Energy Plate Liner, remove the release paper and press the adhesive bottom into place. Pressure is essential for gaining maximum adhesion to the substrate. Continue with your frame construction.

INSTALLATION BELOW 40°:

- Keep Protecto Energy Plate Liner in a warm heated space above 60°F before use.
- Prime the top of the foundation with #100 Primer* and allow primer to tack up. Do not cover wet primer.
- Peel and stick the Protecto Energy Plate Liner in place.

*Note: Protecto Wrap Protecto-Tak 16.25 oz. spray adhesive may be used in place of #100 Primer.

AVAILABLE SIZES

3 ¹/₂" x 25' Roll 5 ¹/₂" x 25' Roll



Protecto Wrap Company 1955 S. Cherokee Street • Denver, CO 80223 (800) 759-9727 • www.ProtectoWrap.com



PEPL-200 (04-17)